

SOLAR-200-TRIO

















Ceiling Light

Description

The SOLAR-RND range of surface mounted LED ceiling lights feature a simple, round and unobtrusive design while providing a 120° beam of uniform light-output through the use of high intensity SMDs (Surface Mounted Diodes).

The SOLAR-RND is constructed from polycarbonate and rated at IP54, making it ideal for usage in damp locations and in dwellings located close to coastal areas.

SOLAR-RND LED ceiling lights are available now with TRIO, the added option of changing the colour temperature output of the downlight with a dip switch at the back of the fitting. All models come complete with driver, (fully dimmable with suitable dimmers) have a lifetime of 40,000 hours and are backed by our Three Year Replacement Warranty.







Specification Features

Input Voltage: AC 240V Power (W): 15W IP rating (IP): IP54

Lumens (lm): Warm White 3000K - 1350lm

Neutral White - 1400lm White 5700K - 1450lm

LED type: SMD

CCT: 3000K - 4000K -5700K (Switchable)


CRI: ≥80

Beam angle (°): 120°

Dimmable: Yes**

Lifespan (hrs): 40,000hrs

Diagrams / Additional



Item No.	Variant	Colour
SOLAR-RND-200-TRIO	20938	White
	20939	Black

^{**} Tested on the Domus Dimmer Series. May work on others but not tested.