

NO UV/IR

HYDRO-120 LED Batten

Description

The HYDRO LED Weatherproof Batten series is a direct replacement to traditional T8 and T5 Fluorescent battens. Custom designed to colour match concrete ceilings, and incorporating a "quick fix" solution to allow for ease and speed of installation. Constructed from high-quality and high impact resistant polycarbonate, with a high transparency frosted polycarbonate diffuser. Available in 600mm and 1200mm lengths, as well as Tricolour switchable: choose between Warm White 3000K, Neutral White 4000K, or White 5500K colour temperatures with the flick of a dip switch.. Suitable for domestic applications such as underground basements, garages, and outdoor areas. Also commercially for underground carparks. Choose between attached grey plastic clips or supplied Stainless Steel clips depending on your installation preference.

ies

65

(10

LED

3yr

Specification Features

Input Voltage:	240V
Power (W):	20-40W (Switchable)
IP rating (IP):	IP65
Lumens (lm):	Warm White 3000K - 3867lm
	Neutral White 4000K - 4362lm
	White 5500K - 4212lm
LED type:	SMD
CCT:	3000K - 4000K - 5500K (Switchable)
CRI:	≥82
Beam angle (°):	120°
Dimmable:	No
Lifespan (hrs):	50,000hrs
Installation:	Surface mounted or suspended

Trio Dip Switch Technology

Variant

66017


CCT

TRIO

Item No.

HYDRO-1

Diagrams / Additional



Domus Lighting 29-31 Richland Street. Kingsgrove NSW 2208 | Phone: (02) 9554 9600 | Fax: (02) 9554 9433 | email: enquiries@domuslighting.com Specification subject to change without prior notice.